



Omnidirectional Terminal Antenna



- Model: FTQ-0204ZD01A
- Name: Omnidirectional Terminal Antenna
- Freq.Range: 200 to 430 MHz
- Communications system: VHF/UHF
- Application scenario:
Wireless data and image transmission,
Terminal communication equipment

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

| | |
|-------------------------|-----------------------|
| Freq.Range-MHz | 200 to 430 |
| Bandwidth-MHz | 230 |
| Gain-dBi | 1 【Typical value】 |
| Half-power beam width-° | H: 360 E: 45 |
| VSWR | ≤ 3.5 【Typical value】 |
| Impedance-Ω | 50 |
| Polarization | Vertical |
| Max.Power-W | 20 |

Mechanical Specifications

| | |
|----------------------------|--|
| Connector | TNC male or N male |
| Dimension-MM | About Φ19×735 |
| Weight-G | About 180 |
| Radome material | ABS |
| Radome color | Black |
| Operational Temperature-°C | -40 to 60 |
| Storage Temperature-°C | -50 to 85 |
| Relative Humidity-% | 5 to 95 |
| Mounting way | Install directly on the equipment |
| Remark | With gooseneck structure at the bottom ,it can be bent |