



# Omnidirectional Ring Array Antenna



- Model: FTQ-02HZ12A
- Name: Omnidirectional Ring Array Antenna
- Freq.Range: 220 to 290 MHz
- Communications system: VHF/UHF,  
Wireless data transmission station
- Application scenario:  
Long-distance communication,  
Wireless data and image transmission,  
Outdoor signal omnidirectional coverage

Tip: Pictures are for reference only.  
Please refer to physical objects.

Electrical Specifications	
Freq.Range-MHz	220 to 290
Bandwidth-MHz	9
Polarization	Vertical
Gain-dBi	Omnidirectional: 12 / Directional: 15
Horizontal Beamwidth-°	360
Vertical Beamwidth-°	6.5
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	500

Mechanical Specifications	
Connector	SL16 female or Customized
Connector Position	Cable outgoing
Cable Length-CM	40CM or Customized
Length-M	About 8.4
Weight-KG	About 18.7
Backbone material	Aluminium alloy
Backbone color	Silver gray
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ50 to 65

Note: in order to facilitate packaging and transportation, the main antenna pole is divided into four sections, and the solid and reliable connection between the four sections is ensured through special joints.



## Installation Demonstrations

