



Omnidirectional Ceiling Antenna



- Model: FTQ-0309XD0203A
- Name: Omnidirectional Ceiling Antenna
- Freq.Range: 351 to 366 and 698 to 960 MHz
- Communications system: VHF/UHF,
Indoor distributed communication system
Wireless trunking communication system
- Application scenario:
Wireless data and image transmission,
Indoor signal omnidirectional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications		
Freq.Range-MHz	351 to 366	698 to 960
Bandwidth-MHz	15	262
Horizontal Beamwidth-°	360	
Vertical Beamwidth-°	85	70
Gain-dBi	2.15	3
Polarization	Vertical	
VSWR	≤ 1.5	≤ 2.0
Impedance-Ω	50	
Max.Power-W	50	

Mechanical Specifications	
Connector	N female or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About Φ320×60
Weight-G	About 800
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Ceiling Mounting



Installation Demonstrations

