



Omnidirectional Mobile Antenna



- Model: FTQ-03CT06CN
- Name: Omnidirectional Mobile Antenna
- Freq.Range: 330 to 390 MHz
- Communications system: VHF/UHF,
Wireless data transmission station,
Wireless trunking communication system
- Application scenario: Client antenna,
Vehicle-mounted mobile communication,
Wireless data and image transmission

Tip: Pictures are for reference only.
Please refer to physical objects.

| Electrical Specifications | |
|---------------------------|------------|
| Freq.Range-MHz | 330 to 390 |
| Bandwidth-MHz | 16 |
| Gain-dBi | 5.5 |
| VSWR | ≤ 1.5 |
| Impedance-Ω | 50 |
| Polarization | Vertical |
| Horizontal Beamwidth-° | 360 |
| Max.Power-W | 100 |

| Mechanical Specifications | |
|----------------------------|--|
| Connector | N male |
| Length-CM | About 120 |
| Weight-G | About 200 |
| Operational Temperature-°C | -40 to 60 |
| Storage Temperature-°C | -55 to 85 |
| Relative Humidity-% | 5 to 95 |
| Rated Wind Velocity-M/S | 60 |
| Remark | Working with a magnetic mount, the cable length and the connector can be customized. |