



Directional Wall Mounted Antenna



- Model: FTD-04BG06V90B
- Name: Directional Wall Mounted Antenna
- Freq.Range: 400 to 480 MHz
- Communications system: VHF/UHF,
Wireless data transmission station,
Wireless trunking communication system,
Indoor distributed communication system
- Application scenario:
Indoor signal directional coverage,
Wireless data and image transmission

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	400 to 480
Bandwidth-MHz	40
Gain-dBi	5±1
Beam Electrical Downtilt-°	0
Half-power beam width-°	H:90±15 / E:85±15
F/B-dB	≥ 15
Polarization	Vertical
VSWR	≤ 2.5
Impedance-Ω	50
Max.Power-W	50

Mechanical Specifications

Connector	N female or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-M	About 210×180×45
Weight-KG	About 1
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Wall mounting



Installation Demonstrations

