



# Omnidirectional Ring Array Antenna



- Model: FTQ-04HZ09A
- Name: Omnidirectional Ring Array Antenna
- Freq.Range: 400 to 480 MHz
- Communications system: VHF/UHF,  
Wireless data transmission station,  
Wireless trunking communication system,  
Wireless intercom communication system
- Application scenario: Wireless video link,  
Long-distance communication,  
Wireless data and image transmission,  
Outdoor signal omnidirectional coverage

Tip: Pictures are for reference only.  
Please refer to physical objects.

Electrical Specifications	
Freq.Range-MHz	400 to 480
Bandwidth-MHz	16
Polarization	Vertical
Gain-dBi	Omnidirectional: 9 / Directional: 12
Horizontal Beamwidth-°	360
Vertical Beamwidth-°	13
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	500

Mechanical Specifications	
Connector	SL16 female or Customized
Connector Position	Cable outgoing
Cable Length-CM	40CM or Customized
Length-M	About 2.5
Weight-KG	About 6
Backbone material	Aluminium alloy
Backbone color	Silver gray
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ50 to 65

Note: in order to facilitate packaging and transportation, the main antenna pole is divided into upper and lower sections, and a special joint is used to ensure a solid and reliable connection between the two sections.



## Installation Demonstrations

