

Omnidirectional Terminal Antenna

• Model: FTQ-04ZD04B

Name: Omnidirectional Terminal Antenna

• Freq.Range: 400 to 480 MHz

Communications system: VHF/UHF,
Wireless data transmission station,
Wireless trunking communication system,
Wireless intercom communication system,
Wireless measurement and
control communication system

• Application scenario:

Wireless data and image transmission, Terminal communication equipment

Tip: Pictures are for reference only. Please refer to physical objects.

| Electrical Specifications | |
|---------------------------|------------|
| Freq.Range-MHz | 400 to 480 |
| Bandwidth-MHz | 20 |
| Horizontal Beamwidth-° | 360 |
| Gain-dBi | 4 |
| VSWR | ≤ 2.0 |
| Impedance- Ω | 50 |
| Polarization | Vertical |
| Max.Power-W | 20 |

| Mechanical Specifications | |
|----------------------------|--|
| Connector | TNC male |
| Length-CM | About 37 |
| Weight-G | About 50 |
| Radome material | Rubber |
| Radome color | Black |
| Operational Temperature-°C | -40 to 60 |
| Storage Temperature-°C | -50 to 85 |
| Relative Humidity-% | 5 to 95 |
| Mounting way | Install directly on the equipment |
| Remark | Elastic whip structure, bending resistance |