



Omnidirectional Terminal Antenna



- Model: FTQ-0405ZD02E
- Name: Omnidirectional Terminal Antenna
- Freq.Range: 480 to 590 MHz
- Communications system: DTTB,
Wireless digital television system
- Application scenario: Mobile Video,
Wireless data and image transmission,
Terminal communication equipment

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

| | |
|------------------------|------------|
| Freq.Range-MHz | 480 to 590 |
| Bandwidth-MHz | 40 |
| Horizontal Beamwidth-° | 360 |
| Gain-dBi | 2.15 |
| VSWR | ≤ 2.0 |
| Impedance-Ω | 50 |
| Polarization | Vertical |
| Max.Power-W | 20 |

Mechanical Specifications

| | |
|----------------------------|------------------------------------------------------------------|
| Connector | SMA male or Customized 【RPSMA male or TNC male or RPTNC male】 |
| Length-MM | About 138 |
| Weight-G | About 20 |
| Radome material | Rubber |
| Radome color | Black |
| Operational Temperature-°C | -40 to 60 |
| Storage Temperature-°C | -50 to 85 |
| Relative Humidity-% | 5 to 95 |
| Mounting way | Install directly on the equipment |
| Remark | Bottom can be bent 90° or 180° |