



Omnidirectional Antenna



- Model: FTQ-0727QX0204A
- Name: Omnidirectional Antenna
- Freq.Range: 698 to 960 / 1710 to 2170 / 2500 to 2700MHz
- Communications system: WLAN/WIFI, GSM/CDMA/EGSM/DCS1800, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario: Base station antenna, Outdoor signal omnidirectional coverage, Wireless data and image transmission

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	698 to 960	1710 to 2170	2500 to 2700
Bandwidth-MHz	262	460	200
Polarization	Vertical		
Gain-dBi	2	2	3.5
Horizontal Beamwidth-°	360		
Vertical Beamwidth-°	50		
Impedance-Ω	50		
VSWR	≤ 2.5		
Max.Power-W	50		

Mechanical Specifications

Connector	N female
Connector Position	Bottom
Length-MM	About 275
Weight-KG	About 0.2
Radome material	PVC
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ35 to 50



Installation Demonstrations

