



Omnidirectional Ceiling Antenna



- Model: FTQ-0738XD0305B
- Name: Omnidirectional Ceiling Antenna
- Freq.Range: 698 to 960 / 1710 to 2690 / 3300 to 3800 MHz
- Communications system: WLAN/WIFI, GSM/CDMA/EGSM/DCS1800/MMDS/5G, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system, Indoor distributed communication system
- Application scenario: Wireless data and image transmission, Indoor signal omnidirectional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	698 to 960	1710 to 2690	3300 to 3800
Bandwidth-MHz	262	980	500
Horizontal Beamwidth-°	360		
Vertical Beamwidth-°	90	70±10	
Gain-dBi	2	5±0.5	
Polarization	Linear		
VSWR	≤ 1.8		
Impedance-Ω	50		
Max.Power-W	50		

Mechanical Specifications

Connector	2×N female or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About Φ260×15
Weight-G	About 250
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Screwed to the ceiling



Installation Demonstrations

