



Omnidirectional Terminal Antenna



- Model: FTQ-0738ZD0204C
- Name: Omnidirectional Terminal Antenna
- Freq.Range: 698 to 960 / 1710 to 2690 / 3300 to 3800 MHz
- Communications system: WLAN/WIFI, GSM/CDMA/EGSM/DCS1800/MMDS/5G, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario: Wireless data and image transmission, Terminal communication equipment

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	698 to 960	1710 to 2690	3300 to 3800
Bandwidth-MHz	262	980	500
Horizontal Beamwidth-°	360		
Gain-dBi	2.15	2.5	3.5
VSWR	≤ 2.5	≤ 2.0	≤ 2.0
Impedance-Ω	50		
Polarization	Vertical		
Max.Power-W	30		

Mechanical Specifications

Connector	N male
Length-MM	About 180
Weight-G	About 60
Radome material	Rubber
Radome color	Gray
Operational Temperature-°C	-30 to 60
Storage Temperature-°C	-50 to 85
Relative Humidity-%	5 to 95
Mounting way	Install directly on the equipment