



Omnidirectional Terminal Antenna



- Model: FTQ-0738ZD0204R
- Name: Omnidirectional Terminal Antenna
- Freq.Range: 698 to 960 / 1710 to 2690 / 3300 to 3800 MHz
- Communications system: WLAN/WIFI, GSM/CDMA/EGSM/DCS1800/MMDS/5G, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario: Wireless data and image transmission, Terminal communication equipment

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	698 to 960	1710 to 2690	3300 to 3800
Bandwidth-MHz	262	980	500
Horizontal Beamwidth-°	360		
Gain-dBi	2	3	3.5
VSWR	≤ 2.5	≤ 2.0	≤ 2.0
Impedance-Ω	50		
Polarization	Vertical		
Max.Power-W	50		

Mechanical Specifications

Connector	SMA male or Customized
Connector Position	Cable outgoing
Cable Length	2M or Customized
Dimension-MM	About $\Phi 81 \pm 0.2 \times 15 \pm 0.2$
Weight-G	About 170
Radome Material	Rubber
Radome Color	Black
Operational Temperature-°C	-30 to 60
Storage Temperature-°C	-50 to 85
Relative Humidity-%	5 to 95
Mounting way	Perforated screw fixing