



- Model: FT-D-5G-V01
- Name: Built-in Antenna
- Freq.Range: 698 to 960 / 1710 to 2700 / 3300 to 3800 / 5000 to 6000 MHz
- Communications system: WLAN/WIFI/RFID, GSM/CDMA/EGSM/DCS1800/MMDS/5G, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario: Client antenna, Wireless data and image transmission, Internet of Things

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	698 to 960	1710 to 2700	3300 to 3800	5000 to 6000
Bandwidth-MHz	262	990	500	1000
Gain-dBi	2	3	4	5
Horizontal Beamwidth-°	360			
Impedance-Ω	50			
Polarization	Vertical			
VSWR	≤ 4.0			
Max.Power-W	20			

Mechanical Specifications

Connector	2×IPEX4 or Customized
Connector Position	Cable outgoing
Cable Length-CM	26CM or Customized
Dimension-MM	About 49×48×1
Weight-G	About 10
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Double-sided super-adhesive mounted inside the device