



- Model: FTD-0750ID10A6
- Name: Built-in Antenna
- Freq.Range: 703 to 803 / 824 to 960/1710 to 2690 / 3300 to 4200 / 4400 to 5000 MHz
- Communications system: WLAN/WIFI/RFID, GSM/CDMA/EGSM/DCS1800/MMDS/5G, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario: Client antenna, Wireless data and image transmission, Internet of Things

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications					
Freq.Range-MHz	703 to 803	824 to 960	1710 to 2690	3300 to 4200	4400 to 5000
Bandwidth-MHz	100	136	980	900	600
Polarization	Linear	Linear	±45°	Linear	Linear
Gain-dBi	5	7	10	10	10
Half-power beam width-°	H:90 E:90	H:70 E:65	H:35 E:65	H:35 E:65	H:35 E:65
Cross-pol-isolation-dB	/	/	≥20	/	/
F/B	≥10	≥10	≥20	≥20	≥20
Impedance-Ω	50				
VSWR	≤2.0	≤2.0	≤2.0	≤2.0	≤2.0
Max.Power-W	50				
Lightning Protection	DC Grounded				

Mechanical Specifications	
Connector	MCX Bend male or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About 300×250×42
Weight-KG	About 1
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Is installed in the equipment through the fixed hole position