



# Omnidirectional Ceiling Antenna



- Model: FTQ-0760XD0204A
- Name: Omnidirectional Ceiling Antenna
- Freq.Range: 698 to 960 / 1710 to 3800 / 4900 to 5850 MHz
- Communications system: WLAN/WIFI/ISM, GSM/CDMA/EGSM/DCS1800/MMDS/5G, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system, Indoor distributed communication system
- Application scenario: Wireless data and image transmission, Indoor signal omnidirectional coverage

Tip: Pictures are for reference only.  
Please refer to physical objects.

## Electrical Specifications

Freq.Range-MHz	698 to 960	1710 to 3800	4900 to 5850
Bandwidth-MHz	262	2090	950
Horizontal Beamwidth-°	360		
Vertical Beamwidth-°	85	50	30
Gain-dBi	2	3	3.5
Polarization	Vertical		
VSWR	≤ 2.2	≤ 2.0	≤ 2.0
Impedance-Ω	50		
Max.Power-W	50		

## Mechanical Specifications

Connector	N female or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About Φ205×115
Weight-G	About 300
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Screwed to the ceiling



## Installation Demonstrations

