



## Omnidirectional Terminal Antenna



- Model: FTQ-0750ZD0203A
- Name: Omnidirectional Terminal Antenna
- Freq.Range: 698 to 960 / 1710 to 2690 / 3300 to 5000 MHz
- Communications system: WLAN/WIFI/ISM, GSM/CDMA/EGSM/DCS1800/MMDS/5G, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario: Wireless data and image transmission, Terminal communication equipment

Tip: Pictures are for reference only.  
Please refer to physical objects.

### Electrical Specifications

Freq.Range-MHz	698 to 960	1710 to 2690	3300 to 5000
Bandwidth-MHz	262	980	1700
Horizontal Beamwidth-°	360		
Gain-dBi	2.15	2.5	3.0
VSWR	≤ 3.0	≤ 2.5	≤ 2.5
Impedance-Ω	50		
Polarization	Vertical		
Max.Power-W	20		

### Mechanical Specifications

Connector	SMA male or Customized
Length-MM	About 163
Weight-G	About 40
Radome material	Rubber
Radome color	White or Black
Operational Temperature-°C	-30 to 60
Storage Temperature-°C	-50 to 85
Relative Humidity-%	5 to 95
Mounting way	Install directly on the equipment