



Directional Flat Panel Antenna



- Model: FTD-09PB09V60
- Name: Directional Flat Panel Antenna
- Freq.Range: 918 to 938 MHz
- Communications system:CDMA/GSM/RFID, Wireless communication
- Application scenario: Point to point, Point to multipoint, Repeater antenna, Wireless data and image transmission, Outdoor signal directional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	918 to 938
Bandwidth-MHz	20
Polarization	Vertical
Gain-dBi	9
Beam Electrical Downtilt-°	0
Half-power beam width-°	H:60 E:55
F/B-dB	≥ 20
Impedance-Ω	50
VSWR	≤ 1.3
Max.Power-W	50
Lightning Protection	DC Grounded

Mechanical Specifications

Connector	N female
Connector Position	Back
Dimension-MM	About 190×190×40
Weight-KG	About 1
Radome material	ABS
Radome color	White
Mechanical tilt-°	0 to 30
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ35 to 50



Installation Demonstrations

