



Omnidirectional Terminal Antenna



- Model: FTQ-0821ZD02C
- Name: Omnidirectional Terminal Antenna
- Freq.Range: 824 to 960 / 1710 to 2170 MHz
- Communications system: CDMA/GSM/FDD,
Wireless trunking communication system
- Application scenario:
Wireless digital transmission,
Wireless data and image transmission,
Terminal communication equipment

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

| | | |
|------------------------|------------|--------------|
| Freq.Range-MHz | 824 to 960 | 1710 to 2170 |
| Bandwidth-MHz | 136 | 460 |
| Horizontal Beamwidth-° | 360 | |
| Gain-dBi | 2.15 | |
| VSWR | ≤ 2.5 | |
| Impedance-Ω | 50 | |
| Polarization | Vertical | |
| Max.Power-W | 20 | |

Mechanical Specifications

| | |
|----------------------------|-----------------------------------|
| Connector | SMA male |
| Length-MM | About 205 |
| Weight-G | About 40 |
| Radome material | Rubber |
| Radome color | Black |
| Operational Temperature-°C | -40 to 60 |
| Storage Temperature-°C | -50 to 85 |
| Relative Humidity-% | 5 to 95 |
| Mounting way | Install directly on the equipment |