



Camouflage Antenna



- Model: FTD-0825MHSD0710V75
- Name: Camouflage Antenna
- Freq.Range: 824 to 960 / 1710 to 2500 MHz
- Communications system: WLAN/WIFI, GSM/CDMA/EGSM/DCS1800/MMDS, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario:
Cell Signal Coverage,
Outdoor signal directional coverage,
Wireless data and image transmission

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications		
Freq.Range-MHz	824 to 960	1710 to 2500
Bandwidth-MHz	136	790
Polarization	Vertical	
Gain-dBi	7	10
Half-power beam width-°	H:90 E:55	H:75 E:45
F/B-dB	≥ 25	
Impedance-Ω	50	
VSWR	≤ 1.5	
Max.Power-W	100	
Lightning Protection	DC Grounded	

Mechanical Specifications	
Connector	N female or Customized
Connector Position	Cable outgoing
Dimension-MM	About 350×330×135
Weight-KG	About 2
Radome material	ABS
Radome color	Black
Mechanical tilt-°	±45°
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Anchor bolt fixing



Installation Demonstrations

