



• Model: FTD-0827IPB0507V70A

• Name: Built-in Antenna

• Freq.Range: 824 to 960 / 1710 to 2690 MHz

 Communications system: WLAN/WIFI, GSM/CDMA/EGSM/DCS1800/MMDS, TD-SCDMA/WCDMA/TDD&FDD-LTE,

Wireless trunking communication system

• Application scenario:

Wireless data and image transmission, Terminal communication equipment, Internet of Things

Tip: Pictures are for reference only. Please refer to physical objects.

Electrical Specifications		
Freq.Range-MHz	824 to 960	1710 to 2690
Bandwidth-MHz	136	980
Polarization	Vertical	
Gain-dBi	5	7
Beam Electrical Downtilt-°	0	
Horizontal Beamwidth-°	65	75
Vertical Beamwidth-°	55	45
F/B-dB	≥15	≥20
Impedance- $\Omega$	50	
VSWR	≤ 2.5	
Max.Power-W	50	

Mechanical Specifications		
Connector	SMA bend male or Customized	
Connector Position	Cable outgoing	
Cable Length-CM	40CM or Customized	
Dimension-MM	About 170×140×20	
Weight-G	About 200	
Operational Temperature-°C	-40 to 60	
Storage Temperature-°C	-55 to 85	
Relative Humidity-%	5 to 95	
Mounting way	Is installed in the equipment through the fixed hole position	