



Omnidirectional Antenna



- Model: FTQ-0727QX0406B
- Name: Omnidirectional Antenna
- Freq.Range: 698 to 960 / 1710 to 2700MHz
- Communications system: WLAN/WIFI, GSM/CDMA/EGSM/DCS1800, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario: Base station antenna, Outdoor signal omnidirectional coverage, Wireless data and image transmission

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications		
Freq.Range-MHz	698 to 960	1710 to 2700
Bandwidth-MHz	262	990
Polarization	Vertical	
Gain-dBi	4	6
Horizontal Beamwidth-°	360	
Vertical Beamwidth-°	35	
Impedance-Ω	50	
VSWR	≤ 2.0	
Max.Power-W	50	

Mechanical Specifications	
Connector	N female
Connector Position	Bottom
Dimension-MM	About Φ76×680
Weight-KG	About 1.9
Radome material	PVC
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ40 to 90



Installation Demonstrations

