



Directional Flat Panel Antenna



- Model: FTD-1314PB14V35
- Name: Directional Flat Panel Antenna
- Freq.Range: 1300 to 1400 MHz
- Communications system:
 - Radio positioning system,
 - Navigation communication system,
 - Microwave communication system
- Application scenario:
 - Point to point, Point to multipoint,
 - Wireless data and image transmission,
 - Outdoor signal directional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications	
Freq.Range-MHz	1300 to 1400
Bandwidth-MHz	20
Polarization	Vertical or Horizontal
Gain-dBi	13.5
Beam Electrical Downtilt-°	0
Half-power beam width-°	H:35 E:33
F/B-dB	≥ 20
Impedance-Ω	50
VSWR	≤ 1.7
Max.Power-W	50
Lightning Protection	DC Grounded

Mechanical Specifications	
Connector	N female
Connector Position	Back
Dimension-MM	About 306×306×25
Weight-KG	About 1.4
Radome material	ABS
Radome color	White
Mechanical tilt-°	0 to 60
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ40 to 50



Installation Demonstrations

