



Directional Parabolic Antenna



- Model: FTD-1415PW26V18
- Name: Directional Parabolic Antenna
- Freq.Range: 1400 to 1550MHz
- Communications system:
 - Microwave communication system,
 - Wireless trunking communication system
- Application scenario:
 - Point to point, Point to multipoint,
 - Wireless bridging, Remote communication,
 - Wireless data and image transmission

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications	
Freq.Range-MHz	1400 to 1550
Bandwidth-MHz	150
Polarization	Vertical
Gain-dBi	26
Half-power beam width-°	H:7.5 E:7.5
F/B-dB	≥ 30
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	100
Lightning Protection	DC Grounded

Mechanical Specifications	
Connector	N female or Customized
Connector Position	Cable outgoing
Cable Length-CM	40CM or Customized
Diameter-M	About Φ1.8
Weight-KG	About 30
Radome material	Aluminium alloy
Radome color	Gray
Mechanical tilt-°	0 to 30
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ50 to 70



Installation Demonstrations

