



Directional Flat Panel Antenna



- Model: FTD-1415PB09V65
- Name: Directional Flat Panel Antenna
- Freq.Range: 1400 to 1500 MHz
- Communications system:
 - Microwave communication system,
 - Broadband digital trunking private network
- Application scenario:
 - Point to point, Point to multipoint,
 - Wireless data and image transmission,
 - Outdoor signal directional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications	
Freq.Range-MHz	1400 to 1500
Bandwidth-MHz	100
Polarization	Vertical
Gain-dBi	9
Beam Electrical Downtilt-°	0
Half-power beam width-°	H:65 E:55
F/B-dB	≥ 20
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	50
Lightning Protection	DC Grounded

Mechanical Specifications	
Connector	N female
Connector Position	Bottom
Dimension-MM	About 223×194×46
Weight-KG	About 1.1
Radome material	ABS
Radome color	White
Mechanical tilt-°	-20 to 20
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ35 to 50



Installation Demonstrations

