




GPS/GSM Antenna



- Model: GQ1509QX05VU
- Name: Omnidirectional Antenna
- Freq.Range: 1570 to 1580 / 863 to 930 MHz
- Communications system:
GPS Satellite communication,
Navigation communication system,
GSM Mobile communication
- Application scenario:
Radio positioning system,
Outdoor signal omnidirectional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	1570 to 1580	863 to 930
Communications system	GPS	GSM
Bandwidth-MHz	10	67
Gain-dBi	5	5
Polarization	Vertical	Vertical
VSWR	≤ 1.5	≤ 1.5
Impedance-Ω	50	
Max.Power-W	50	

Mechanical Specifications

Connector	2×RPSMA male or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About Φ76×500
Weight-KG	About 2
Radome material	PVC
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-50 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ40 to 90
Remark	UBNT equipment mounting base is standard



Installation Demonstrations

