



Omnidirectional Ceiling Antenna



- Model: FTQ-152458XD02A
- Name: Omnidirectional Ceiling Antenna
- Freq.Range: 1560 to 1620 / 2400 to 2500 / 5150 to 5850 MHz
- Communications system: WLAN/WIFI/ISM, GPS/Navigation communication system, Indoor distributed communication system
- Application scenario: Wireless data and image transmission, Indoor signal omnidirectional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	1560 to 1620	2400 to 2500	5150 to 5850
Bandwidth-MHz	60	100	700
Horizontal Beamwidth-°	360		
Vertical Beamwidth-°	85	55	45
Gain-dBi	2.15		
Polarization	Vertical		
VSWR	≤ 2.0		
Impedance-Ω	50		
Max.Power-W	50		

Mechanical Specifications

Connector	N female or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About Φ165.5×94
Weight-G	About 300
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Nuts fixed to the ceiling



Installation Demonstrations

