



Directional Flat Panel Antenna



- Model: FTD-1718PB09DP60A
- Name: Directional Flat Panel Antenna
- Freq.Range: 1710 to 1880 MHz
- Communications system:
GSM1800/FDD,
Wireless access communication system
- Application scenario:
Point to point, Point to multipoint,
Wireless data and image transmission,
Outdoor signal directional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications	
Freq.Range-MHz	1710 to 1880
Bandwidth-MHz	170
Polarization	±45°
Gain-dBi	9
Beam Electrical Downtilt-°	0
Half-power beam width-°	H:55±5 E:55±5
Cross-pol-isolation-dB	≥ 25
F/B-dB	≥ 20
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	50
Lightning Protection	DC Grounded

Mechanical Specifications	
Connector	2×N female
Connector Position	Back
Dimension-MM	About 190×190×40
Weight-KG	About 1
Radome material	ABS
Radome color	White
Mechanical tilt-°	-20 to 20
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ35 to 50



Installation Demonstrations

