



Camouflage Antenna



- Model: FTD-1727MHSD12V33
- Name: Camouflage Antenna
- Freq.Range: 1710 to 2700 MHz
- Communications system: WLAN/WIFI, TD-SCDMA/WCDMA/TDD&FDD-LTE, Mobile communication wireless network optimization
- Application scenario: Cell Signal Coverage, Outdoor signal directional coverage, Wireless data and image transmission

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications	
Freq.Range-MHz	1710 to 2700
Bandwidth-MHz	990
Polarization	Vertical
Gain-dBi	11.5
Half-power beam width-°	H:33 E:60
F/B-dB	≥ 20
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	50
Lightning Protection	DC Grounded

Mechanical Specifications	
Connector	N female or Customized
Connector Position	Cable outgoing
Dimension-MM	About 360×340×125
Weight-KG	About 2
Radome material	ABS
Radome color	Black
Mechanical tilt-°	±45°
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Waterproof level	IP65
Rated Wind Velocity-M/S	60
Mounting way	Anchor bolt fixing



Installation Demonstrations

