



Omnidirectional Ceiling Antenna



- Model: FTQ-1925XD03A
- Name: Omnidirectional Ceiling Antenna
- Freq.Range: 1920 to 2170 / 2300 to 2500 MHz
- Communications system: WLAN/WIFI, TD-SCDMA/WCDMA/FDD/CDMA2000, Indoor distributed communication system
- Application scenario: Wireless data and image transmission, Indoor signal omnidirectional coverage

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	1920 to 2170	2300 to 2500
Bandwidth-MHz	250	200
Horizontal Beamwidth-°	360	
Vertical Beamwidth-°	60	
Gain-dBi	3	
Polarization	Vertical	
VSWR	≤ 1.5	
Impedance-Ω	50	
Max.Power-W	20	

Mechanical Specifications

Connector	2×N female or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About Φ145×35
Weight-G	About 250
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Nuts fixed to the ceiling



Installation Demonstrations

