



# Omnidirectional Fiberglass Antenna



- Model: FTQ-2327QX06B
- Name: Omnidirectional Fiberglass Antenna
- Freq.Range: 2300 to 2700 MHz
- Communications system: MMDS/WLAN/WIFI, Radio positioning system, Microwave communication system, 2.4G Spread Spectrum Communication
- Application scenario: Point to multipoint, Base station antenna, Wireless data and image transmission, Outdoor signal omnidirectional coverage, Public wireless hotspot coverage

Tip: Pictures are for reference only.  
Please refer to physical objects.

## Electrical Specifications

Freq.Range-MHz	2300 to 2700
Bandwidth-MHz	400
Polarization	Vertical
Gain-dBi	6
Horizontal Beamwidth-°	360
Vertical Beamwidth-°	25
Impedance-Ω	50
VSWR	≤ 1.7
Max.Power-W	50

## Mechanical Specifications

Connector	N female
Connector Position	Bottom
Length-MM	About 420
Weight-KG	About 0.3
Radome material	Fiberglass
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ30 to 50