



Directional MIMO Wall Mounted Antenna



- Model: FTD-2458MBG0606VH120-4
- Name: MIMO Wall Mounted Antenna
- Freq.Range: 2400 to 2500 / 5150 to 5850 MHz
- Communications system:
2.4/5.8GHz WLAN/WIFI/WIMAX/ISM,
Indoor distributed communication system,
Spread Spectrum Communication
- Application scenario:
Indoor signal directional coverage,
Public wireless hotspot coverage,
IEEE802.11a/b/g/n

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2500	5150 to 5850
Bandwidth-MHz	100	700
Polarization	Vertical and Linear	
Gain-dBi	6	6
Half-power beam width-°	H:105 E:70	H:120 E:60
Cross-pol-isolation-dB	≥ 23	
F/B-dB	≥ 18	
Impedance-Ω	50	
VSWR	≤ 2.0	
Max.Power-W	50	
Lightning Protection	DC Grounded	

Mechanical Specifications

Connector	4×RPTNC male or Customized
Connector Position	Cable outgoing
Cable Length-CM	90CM or Customized
Dimension-M	About 245×142×36
Weight-KG	About 0.5
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Wall mounting



Installation Demonstrations

