



Omnidirectional MIMO Mobile Antenna



- Model: FTQ-2458MCT0304V3A
- Name: Omnidirectional MIMO Mobile Antenna
- Freq.Range: 2400 to 2500 / 5150 to 5850 MHz
- Communications system:
2.4/5.8GHz WLAN/WIFI/WIMAX/LMDS,
Wireless access communication system
- Application scenario: Client antenna,
Vehicle-mounted mobile communication,
Wireless data and image transmission,
IEEE802.11a/b/e/g/n

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2500	5150 to 5850
Bandwidth-MHz	100	700
Polarization	3×Vertical	
Gain-dBi	3	4
Impedance-Ω	50	
VSWR	≤ 1.5	≤ 2.0
Max.Power-W	20	

Mechanical Specifications

Connector	3×RPSMA male or Customized
Connector Position	Cable outgoing
Cable Length-M	3M or Customized
Dimension-MM	About Φ124×160
Weight-KG	About 0.9
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Magnetic adsorption