



MIMO Omnidirectional Antenna



- Model: FTQ-2458MQX0608V6AS
- Name: MIMO Omnidirectional Antenna
- Freq.Range: 2400 to 2500 / 5150 to 5850 MHz
- Communications system:
2.4/5.8GHz WLAN/WIFI/ISM/WIMAX,
Spread Spectrum Communication
- Application scenario:
Point to multipoint, Base station antenna,
Wireless data and image transmission,
Outdoor signal omnidirectional coverage,
Public wireless hotspot coverage,
IEEE802.11a/b/e/g/n

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2500	5150 to 5850
Bandwidth-MHz	100	700
Polarization	Vertical	Vertical
Gain-dBi	6	8
Half-power beam width-°	H:360 E:40	H:360 E:17
Cross-pol-isolation-dB	≥25	
Impedance-Ω	50	
VSWR	≤ 1.5	≤ 2.0
Max.Power-W	20	

Mechanical Specifications

Connector	6×RPSMA Female
Connector Quantity	Three 2.4GHz Connector and Three 5.8GHz Connector
Connector Position	Bottom
Dimension-MM	About Φ145×185
Weight-KG	About 0.8
Radome material	ABS or PC
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ40 to 50



Installation Demonstrations

