



Omnidirectional Antenna



- Model: FTQ-2458QX0608CN
- Name: Omnidirectional Antenna
- Freq.Range: 2400 to 2500 / 5150 to 5850 MHz
- Communications system:
2.4/5.8GHz WLAN/WIFI/ISM/UNII,
Spread Spectrum Communication,
Vehicle-mounted mobile communication
- Application scenario:
Wireless data and image transmission,
Terminal communication equipment

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2483	5150 to 5350	5350 to 5850
Bandwidth-MHz	83	200	500
Gain-dBi	6	6	8
Half-power beam width-°	H:360 E:22	H:360 E:22	H:360 E:10
VSWR	≤ 1.5	≤ 2.5	
Impedance-Ω	50		
Polarization	Vertical		
Max.Power-W	50		

Mechanical Specifications

Connector	N male
Connector Position	Bottom
Dimension-MM	About Φ28×770
Weight-G	About 250
Radome material	PVC
Radome color	White
Operational Temperature-°C	-10 to 55
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Working with N-type seat