



# Omnidirectional Terminal Antenna



- Model: FTQ-2458ZD0306A
- Name: Omnidirectional Terminal Antenna
- Freq.Range: 2400 to 2483 / 5150 to 5850 MHz
- Communications system:  
2.4/5.8GHz WLAN/WIFI/ISM/UNII,  
Spread Spectrum Communication
- Application scenario:  
Wireless data and image transmission,  
Terminal communication equipment

Tip: Pictures are for reference only.  
Please refer to physical objects.

Electrical Specifications		
Freq.Range-MHz	2400 to 2483	5150 to 5850
Bandwidth-MHz	83	700
Horizontal Beamwidth-°	360	
Gain-dBi	3	6
VSWR	≤ 2.0	
Impedance-Ω	50	
Polarization	Vertical	
Max.Power-W	10	

Mechanical Specifications	
Connector	RPSMA male or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About 65×40×5
Weight-G	About 60
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-50 to 85
Relative Humidity-%	5 to 95
Mounting way	Double-sided super-adhesive adhesive is pasted on the equipment surface