



Omnidirectional Terminal Antenna



- Model: FTQ-24ZD05E
- Name: Omnidirectional Terminal Antenna
- Freq.Range: 2400 to 2483 MHz
- Communications system:
2.4GHz WLAN/WIFI/ISM/UNII,
Spread Spectrum Communication
- Application scenario:
Wireless data and image transmission,
Terminal communication equipment

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

| | |
|------------------------|--------------|
| Freq.Range-MHz | 2400 to 2483 |
| Bandwidth-MHz | 83 |
| Horizontal Beamwidth-° | 360 |
| Gain-dBi | 5 |
| VSWR | ≤ 1.8 |
| Impedance-Ω | 50 |
| Polarization | Vertical |
| Max.Power-W | 20 |

Mechanical Specifications

| | |
|----------------------------|-----------------------------------|
| Connector | SMA male or Customized |
| Length-MM | About 185 |
| Weight-G | About 40 |
| Radome material | Rubber |
| Radome color | Black |
| Operational Temperature-°C | -40 to 60 |
| Storage Temperature-°C | -50 to 85 |
| Relative Humidity-% | 5 to 95 |
| Mounting way | Install directly on the equipment |
| Remark | Bottom fixed bent 90° |