



Omnidirectional Ceiling Antenna



Tip: Pictures are for reference only.
Please refer to physical objects.

- Model: FTQ-24XD03B
- Name: Omnidirectional Ceiling Antenna
- Freq.Range: 2400 to 2500 MHz
- Communications system:
 - 2.4GHz WLAN/WIFI,
 - Indoor distributed communication system,
 - 2.4GHz Spread Spectrum Communication
- Application scenario:
 - Wireless data and image transmission,
 - Indoor signal directional coverage,
 - Public wireless hotspot coverage,
 - IEEE802.11b/g

Electrical Specifications

| | |
|------------------------|--------------|
| Freq.Range-MHz | 2400 to 2500 |
| Bandwidth-MHz | 100 |
| Horizontal Beamwidth-° | 360 |
| Vertical Beamwidth-° | 85 |
| Gain-dBi | 3 |
| Polarization | Vertical |
| VSWR | ≤ 1.5 |
| Impedance-Ω | 50 |
| Max.Power-W | 20 |

Mechanical Specifications

| | |
|----------------------------|---------------------------|
| Connector | N female or Customized |
| Connector Position | Cable outgoing |
| Cable Length-CM | 30CM or Customized |
| Dimension-MM | About Φ124×47 |
| Weight-G | About 150 |
| Radome material | ABS |
| Radome color | White |
| Operational Temperature-°C | -40 to 60 |
| Storage Temperature-°C | -55 to 85 |
| Relative Humidity-% | 5 to 95 |
| Mounting way | Nuts fixed to the ceiling |



Installation Demonstrations

