



Omnidirectional Fiberglass Antenna



- Model: FTQ-24QX08ATN
- Name: Omnidirectional Fiberglass Antenna
- Freq.Range: 2400 to 2483 MHz
- Communications system:
2.4GHz WLAN/WIFI/ISM/UNII,
Spread Spectrum Communication
- Application scenario:
Terminal communication equipment,
Wireless data and image transmission,
Public wireless hotspot coverage,
IEEE802.11b/g

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2483
Bandwidth-MHz	83
Gain-dBi	8
Horizontal Beamwidth-°	360
Vertical Beamwidth-°	16
VSWR	≤ 1.5
Impedance-Ω	50
Polarization	Vertical
Max.Power-W	50

Mechanical Specifications

Connector	N male
Connector Position	Bottom
Dimension-MM	About Φ21×546
Weight-G	About 500
Radome material	Fiberglass
Radome color	Gray
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Working with N-type seat
Remark	Bottom spring structure anti-collision