



Directional Wall Mounted Antenna



Tip: Pictures are for reference only.
Please refer to physical objects.

- Model: FTD-24BG12V60
- Name: Directional Wall Mounted Antenna
- Freq.Range: 2400 to 2500 MHz
- Communications system:
2.4GHz WLAN/WIFI/ISM/WIMAX,
Indoor distributed communication system,
Spread Spectrum Communication
- Application scenario:
Indoor signal directional coverage,
Wireless data and image transmission,
Public wireless hotspot coverage,
IEEE802.11b/g

Electrical Specifications

Freq.Range-MHz	2400 to 2500
Bandwidth-MHz	100
Polarization	Vertical
Gain-dBi	12
Half-power beam width-°	H:60 E:25
F/B-dB	≥ 19
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	50
Lightning Protection	DC Grounded

Mechanical Specifications

Connector	N Female or Customized
Connector Position	Cable outgoing
Cable Length-CM	30CM or Customized
Dimension-MM	About 210×180×44
Weight-KG	About 0.4
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Wall mounting



Installation Demonstrations

