



Antenna with mounting cavity



- Model: FTQ-24CXD05HH360
- Name: Antenna with mounting cavity
- Freq.Range: 2400 to 2500 MHz
- Communications system:
2.4GHz WLAN/WIFI/ISM/UNII/RFID,
Spread Spectrum Communication,
Indoor distributed communication system
- Application scenario:
Wireless data and image transmission,
Public wireless hotspot coverage,
Indoor signal omnidirectional coverage,
IEEE802.11b/g

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2500
Bandwidth-MHz	100
Polarization	Horizontal and Horizontal
Gain-dBi	5
Half-power beam width-°	H:360 E:80
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	20

Mechanical Specifications

Connector	2×U.FL or Customized
Cable Length-CM	10CM or Customized
Antenna Dimension-MM	About Φ180×35
Weight-G	About 150
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-50 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Nuts fixed to the ceiling