



Directional Flat Panel Antenna



Tip: Pictures are for reference only.
Please refer to physical objects.

- Model: FTD-24PB17VH20
- Name: Directional Flat Panel Antenna
- Freq.Range: 2400 to 2500 MHz
- Communications system:
 - 2.4GHz WLAN/WIFI/ISM/UNII,
 - 2.4GHz Spread Spectrum Communication
- Application scenario:
 - Point to point, Point to multipoint,
 - Wireless data and image transmission,
 - Outdoor signal directional coverage,
 - Public wireless hotspot coverage,
 - Wireless bridging, IEEE802.11b/g

Electrical Specifications

Freq.Range-MHz	2400 to 2500
Bandwidth-MHz	100
Polarization	Vertical or Horizontal
Gain-dBi	17
Beam Electrical Downtilt-°	0
Half-power beam width-°	H:20 E:20
Cross-pol-isolation-dB	≥ 25
F/B-dB	≥ 25
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	50
Lightning Protection	DC Grounded

Mechanical Specifications

Connector	2×N female
Connector Position	Back
Dimension-MM	About 325×325×65
Weight-KG	About 2
Radome material	ABS
Radome color	Gray
Mechanical tilt-°	0 to 30
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ35 to 50



Installation Demonstrations

