



Omnidirectional MIMO Mobile Antenna



- Model: FTQ-24MCT05V2
- Name: Omnidirectional MIMO Mobile Antenna
- Freq.Range: 2400 to 2500 MHz
- Communications system:
2.4GHz WLAN/WIFI/ISM/MIMO,
Spread Spectrum Communication
- Application scenario:
Client antenna,
Vehicle-mounted mobile communication,
IEEE802.11b/g

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2500
Bandwidth-MHz	100
Polarization	2×Vertical
Gain-dBi	5
Half-power beam width-°	H:360 E:30
Cross-pol-isolation-dB	≥20
VSWR	≤ 1.5
Impedance-Ω	50
Max.Power-W	20

Mechanical Specifications

Connector	2×MMCX Bend male 【IN】
Out Connector	PG16
Dimension-MM	About Φ145×340
Radome color	White
Weight-KG	About 1.8
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Magnetic adsorption
Magnetic sucker lead-M	3M or Customized
Magnetic sucker lead Connector	SMA male or Customized
Remark	RF motherboard can be built in