



MIMO Omnidirectional Antenna



- Model: FTQ-24MQX08V2BU
- Name: MIMO Omnidirectional Antenna
- Freq.Range: 2400 to 2500 MHz
- Communications system:
2.4GHz WLAN/WIFI/ISM/MIMO,
Spread Spectrum Communication
- Application scenario:
Point to multipoint, Base station antenna,
Wireless data and image transmission,
Outdoor signal omnidirectional coverage,
Public wireless hotspot coverage,
IEEE802.11b/g

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2500
Bandwidth-MHz	100
Polarization	2×Vertical
Gain-dBi	8
Half-power beam width-°	H:360 E:20
Cross-pol-isolation-dB	≥25
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	50

Mechanical Specifications

Connector	2×RPSMA male
Connector Position	Bottom
Dimension-MM	About Φ75×465
Weight-KG	About 1.6
Radome material	PVC
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ40 to 90
Remark	UBNT equipment mounting base is standard



Installation Demonstrations

