



Omnidirectional MIMO Ceiling Antenna



- Model: FTQ-24MXD03V2
- Name: Omnidirectional MIMO Ceiling Antenna
- Freq.Range: 2400 to 2500 MHz
- Communications system:
 - 2.4GHz WLAN/WIFI/WIMAX/MIMO,
 - Spread Spectrum Communication
 - Indoor distributed communication system
- Application scenario:
 - Wireless data and image transmission,
 - Indoor signal omnidirectional coverage,
 - Public wireless hotspot coverage,
 - IEEE802.11b/g

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 2500
Bandwidth-MHz	100
Horizontal Beamwidth-°	360
Vertical Beamwidth-°	85
Polarization	2×Vertical
Gain-dBi	2.5
Impedance-Ω	50
VSWR	≤ 1.5
Max.Power-W	20

Mechanical Specifications

Connector	2×N Female or Customized
Connector Position	Cable outgoing
Cable Length-CM	20CM or Customized
Dimension-MM	About Φ145×42
Weight-G	About 300
Radome material	ABS
Radome color	White
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Mounting way	Nuts fixed to the ceiling



Installation Demonstrations

