



Omnidirectional Mobile Antenna



- Model: FTQ-2460CT03A
- Name: Omnidirectional Mobile Antenna
- Freq.Range: 2400 to 6000 MHz
- Communications system: UWB/5G, 2.4/5.8GHz WLAN/WIFI/ISM/UNII, Spread Spectrum Communication, Wireless trunking communication system
- Application scenario: Client antenna, Vehicle-mounted mobile communication, Wireless data and image transmission, Terminal communication equipment, Internet of Things

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications

Freq.Range-MHz	2400 to 6000
Bandwidth-MHz	3600
Gain-dBi	3
VSWR	≤ 2.0
Impedance- Ω	50
Polarization	Vertical
Horizontal Beamwidth- $^{\circ}$	360
Max.Power-W	50

Mechanical Specifications

Connector	NMO male
Dimension-MM	About $\Phi 35 \times 69$
Weight-KG	About 0.15
Operational Temperature- $^{\circ}\text{C}$	-40 to 60
Storage Temperature- $^{\circ}\text{C}$	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Working with mounts such as magnetic chucks