



Omnidirectional Fiberglass Antenna



- Model: FTQ-4450QX10AN
- Name: Omnidirectional Fiberglass Antenna
- Freq.Range: 4400 to 5000 MHz
- Communications system:5G,
Wireless trunking communication system
- Application scenario:
Terminal communication equipment,
Wireless data and image transmission,
Vehicle-mounted mobile communication

Tip: Pictures are for reference only.
Please refer to physical objects.

| Electrical Specifications | |
|---------------------------|--------------|
| Freq.Range-MHz | 4400 to 5000 |
| Bandwidth-MHz | 600 |
| Gain-dBi | 10 |
| Horizontal Beamwidth-° | 360 |
| Vertical Beamwidth-° | 10.5 |
| VSWR | ≤ 2.0 |
| Impedance-Ω | 50 |
| Polarization | Vertical |
| Max.Power-W | 50 |

| Mechanical Specifications | |
|----------------------------|--------------------------|
| Connector | N male |
| Connector Position | Bottom |
| Dimension-MM | About Φ21×570 |
| Weight-G | About 450 |
| Radome material | Fiberglass |
| Radome color | Gray |
| Operational Temperature-°C | -40 to 60 |
| Storage Temperature-°C | -55 to 85 |
| Relative Humidity-% | 5 to 95 |
| Rated Wind Velocity-M/S | 60 |
| Mounting way | Working with N-type seat |