



# Directional Flat Panel Antenna



Tip: Pictures are for reference only.  
Please refer to physical objects.

- Model: FTD-5158PB14V90C
- Name: Directional Flat Panel Antenna
- Freq.Range: 5150 to 5850 MHz
- Communications system:  
5.1 to 5.8GHz WLAN/WIFI/ISM/UNII,  
5.1 to 5.8GHz Spread Spectrum Communication
- Application scenario:  
Point to point, Point to multipoint,  
Wireless data and image transmission,  
Outdoor signal directional coverage,  
Public wireless hotspot coverage,  
IEEE802.11a/n

Electrical Specifications	
Freq.Range-MHz	5150 to 5850
Bandwidth-MHz	700
Polarization	Vertical
Gain-dBi	14
Beam Electrical Downtilt-°	0
Half-power beam width-°	H:90 E:16
F/B-dB	≥ 25
Impedance-Ω	50
VSWR	≤ 2.0
Max.Power-W	50
Lightning Protection	DC Grounded

Mechanical Specifications	
Connector	N female
Connector Position	Bottom
Dimension-MM	About 223×194×46
Weight-KG	About 1.1
Radome material	ABS
Radome color	White
Mechanical tilt-°	-20 to 20
Operational Temperature-°C	-40 to 60
Storage Temperature-°C	-55 to 85
Relative Humidity-%	5 to 95
Rated Wind Velocity-M/S	60
Mounting way	Mast
Mast Diameter-MM	Φ35 to 50



## Installation Demonstrations

