



- Model: FTQ-0750IQ02A-4
- Name: Built-in Antenna
- Freq.Range: 617 to 960 & 1452 to 5000
/1710 to 4200 / 1452 to 4200 / 4400 to 5000 MHz
- Communications system: WLAN/WIFI/RFID, GSM/CDMA/EGSM/DCS1800/MMDS/5G, TD-SCDMA/WCDMA/TDD&FDD-LTE, Wireless trunking communication system
- Application scenario: Client antenna, Wireless data and image transmission, Internet of Things

Tip: Pictures are for reference only.
Please refer to physical objects.

Electrical Specifications				
Freq.Range-MHz	617 to 960&1452 to 5000	1710 to 4200	1452 to 4200	4400 to 5000
Bandwidth-MHz	343&3548	2490	2748	600
Polarization	Vertical			
Gain-dBi	1&2.5	2	2.5	4
Impedance-Ω	50			
VSWR	≤4.0	≤3.0	≤3.0	≤2.0
Max.Power-W	10			

Mechanical Specifications				
Connector	IPEX	IPEX	IPEX	IPEX
Connector Position	Cable outgoing			
Cable Length-CM	15	15	15	15
Dimension-MM	About 153×115×2.5			
Weight-G	About 30			
Operational Temperature-°C	-40 to 85			
Storage Temperature-°C	-55 to 85			
Relative Humidity-%	5 to 95			
Mounting way	Is installed in the equipment through the fixed hole position			